

## TECHNICAL CHARACTERISTICS

Series of insulators designed to be used as supports or spacers of electrically active parts such as the bars used to create panels.

Made of polyester resin with the addition of glass fibres, they guarantee a high mechanical and electrical resistance over time. Furthermore, the material used is non absorbing and highly self-extinguishing.

On both resting sides the insulators feature a brass or white iron zincate threaded female insert that, by means of different types of special headless screws, allows the coupling with the parts concerned.

Thanks to the special shape of the metallic insert (which differs from the CP-DP series as it protrudes by 2 mm), they are used in those cases when a washer needs to be interposed to increase the contact surface.

- Colour: red RAL-3002 (a different colour can be provided on request in case of large orders)
- Arc resistance: > 180 s - ASTM D-495
- Material: self-extinguishing in class V0 (1.6 mm) according to the UL-94 standard
- Operating temperature: -40 °C ÷ +130 °C
- Water absorption: < 0.2% - ASTM D-570
- Tracking resistance: 3 W/min - ASTM D-2302
- For the fastening please refer to the section "GV series accessories"



## SELECTABLE ELEMENTS CPS SERIES

	Code	Model	Height (mm)	Width (mm)
<b>M5 insert</b>				
	<b>SA676400</b>	CPS2035-05	35	20
<b>M6 insert</b>				
	<b>SA677200</b>	CPS2035-06	35	20
	<b>SA679800</b>	CPS2050-06	50	20
	<b>SA681400</b>	CPS2070-06	70	20
	<b>SA683000</b>	CPS3070-06	70	30
<b>M8 insert</b>				
	<b>SA678000</b>	CPS2035-08	35	20
	<b>SA680600</b>	CPS2050-08	50	20
	<b>SA682200</b>	CPS2070-08	70	20
	<b>SA684800</b>	CPS3070-08	70	30
	<b>SA685500</b>	CPS4070-08	70	40
<b>M10 insert</b>				
	<b>SA686300</b>	CPS4070-10	70	40
<b>M12 insert</b>				
	<b>SA687100</b>	CPS4070-12	70	40

## SELECTABLE ELEMENTS DPS SERIES

	Code	Model	Height (mm)	Width (mm)
<b>M6 insert</b>				
	<b>SA670700</b>	DPS6035-06	34.9	32
<b>M8 insert</b>				
	<b>SA671500</b>	DPS6035-08	34.9	32