

PVC fairleads. They electrically protect wires and passer-by cables through panels and ensure a good seal to dust.


- Material: lead and DEHP free PVC (in compliance with directive 2002/95/EC - RoHS)
- Colour: black
- Operating temperature:  $-10 \div 80^{\circ}\text{C}$
- Hardness: 50 shore A (ISO 768)




## TECHNICAL INFORMATION

### DIMENSIONS (mm)


#### Front view



#### Side view



rounded shape



flat shape

Code	Model	Hole diameter (A) for mounting (mm)	Maximum diameter fairlead (D) (mm)	Hole diameter (d) cable passage (mm)	Maximum thickness fairlead (H) (mm)	Sheet thickness (B) (mm)	Shape
VE357000	10479	28	35	21	2	8	Rounded
VE358800	10460	24	32	15.5	2	8,5	Rounded
VE359600	10438	18	24	16	2	7,5	Flat
VE360400	10445	21	28	16	2	8	Flat
VE361200	10413	18	23	13	2	8	Flat
VE362000	10050	11.5	14.5	8.5	1,2	8	Rounded
VE363800	10031	10	14	6	4	10	Rounded
VE364600	10102	11	15	6	1.5	7,5	Rounded
VE365300	10285	7.5	10	4	3.25	8	Rounded

