

Analog testers

VE 381

Pocket tester to measure direct and alternating voltage, direct current, resistance, battery charge.

- Operating conditions:
 - temperature range: $+5\text{ }^{\circ}\text{C} \div +40\text{ }^{\circ}\text{C}$
 - relative humidity: $< 80\%$
- Power supply: 1 battery 1.5 V AA type
- Fuse: 0.5 A / 250 V (5x20 mm)
- Dimensions: 30x60x95 mm
- Weight: 100 g
- Included accessories: battery, spare fuse, measurement points, instructions for use



Code	Model	Description
VE367900	VE 381	Analog pocket tester

TECHNICAL INFORMATION

Function	Capacity	Full scale precision
Voltage	DC 2.5/10/50/250/500 V	$\pm 4\%$
Voltage	AC 10/50/250/500 V	$\pm 5\%$
Current	DC 0.5/10/250 mA	$\pm 4\%$
Resistance	Ω Rx10/Rx1k (500 Ω f.s.)	
Decibel	dB -20 \div +56 on all scales in V AC	
Batteries test	BAT 1.5 V	

REFERENCE STANDARDS

Compliance with Community Directives:
2006/95/EC (Low Voltage) and 2004/108/EC (E.M.C.)
is declared with reference to the following standards:

- Safety: EN 61010-1
- E.M. Compatibility: EN 61000-6-2 and EN 61000-6-4