

# Analog testers

## VE 382

Tester to measure direct and alternating voltage, direct current, resistance, transistor test, led/diode test, continuity, battery charge, measure in decibels.

- Operating conditions:
  - temperature range: 0 °C ÷ +40 °C
  - relative humidity: < 90%
- Power supply: 2 batteries 1.5 V AA type, 1 9V battery
- Fuse: 0.5 A / 1000V (type FF, 6,3x32mm)
- Dimensions: 154x101x40 mm
- Weight: 275 g
- Included accessories: batteries, spare fuse, measurement points, instructions for use



| Code     | Model  | Description                |
|----------|--------|----------------------------|
| VE368700 | VE 382 | Analog professional tester |

## TECHNICAL INFORMATION

| Function       | Capacity                    | Full scale precision |
|----------------|-----------------------------|----------------------|
| Voltage        | DC 0.1/2.5/10/50/250/1000 V | ± 3%                 |
| Voltage        | AC 10/50/250/1000 V         | ± 4%                 |
| Current        | DC 0.05/2.5/25/250 mA       | ± 3%                 |
| Resistance     | Ω 2k/20k/200k/2M/20M        |                      |
| Decibel        | dB -20 ÷ +62                |                      |
|                | on all scales in V AC       |                      |
| Batteries test | BAT 1.5 V/9 V               |                      |

## REFERENCE STANDARDS

Compliance with Community Directives:  
2014/35/CE (Low Voltage) 2014/30/CE (Electromagnetic compatibility)  
is declared with reference to the following standards:

- Safety: EN 61010-1
- E.M. Compatibility: EN 61000-6-2 and EN 61000-6-4