

Electronic humidistats

HUMI

Flush-mounting humidistat with 2-position selector for humidity control in domestic environments.



- 1 Installation in three modules in built box
- 2 Relay status signaling led
- 3 Interchangeable cover in two colours: anthracite grey and white (included in the package)
- 4 Selector with two positions: off, automatic
- 5 Knob of humidity control
- 6 Support adaptable to main civil series


FLUSH- MOUNTING HUMIDISTAT

- Power supply: 230Vac 50/60 Hz
- Consumption: 4VA (0.5W)
- Bistable relay output: 5(3) A / 250Vac
- Regulation range: 30% ÷ 90% RH with fixed differential at 5% RH (centered on the setpoint)
- Minimum time between a switching and the next one: 1 minute
- Failure signaling through flashing led
- Operating temperature: 0 ÷ 50°C
- Storage temperature: -10 ÷ 60°C
- Protection degree: IP40


Code	Model	Description	Colour	Power supply
VE379400	Humi	Flush-mounting	White/Grey	230 V~

DIMENSIONS (mm)


Front view



Side view



CONNECTION DIAGRAM



Adjustable plates

ABB Chiara series	Bticino Livinglight Air series
ABB Mylos series	Bticino Matix series
Ave S44 series	Gewiss Chorus series
Bticino Axolute series	Vimar Eikon series
Bticino Axolute Air series*	Vimar Eikon Evo series
Bticino Light series	Vimar Idea series
Bticino Light tech series	Vimar Plana series
Bticino Living series	Vimar Arké series
Bticino Livinglight series	

* by mount that can be bought separately

For information on how to use different plates, contact the Technical Service

REFERENCES STANDARDS

Compliance with Community Directives:
2014/35/EU (LVD) • 2014/30/EU (EMCD)
is declared in reference to the following standards:
EN 60730-2-13 • EN 60730-2-13