

Digital clamp meter to measure dispersed currents (AC).

- AC dispersed currents measurements
- LCD display: 3 ½ digits, max reading 1999
- Out of scale indication (max 0.4 s)
- Zero regulation: automatic
- Data Hold
- Operating temperature: 0 ÷ +50 °C (<80% RH)
- Storage temperature: -20 °C ÷ +60 °C (<80% RH)
- Power supply: 9 V battery
- Consumption: 1.2 mA DC
- Weight: 200 g
- Jaw opening: Ø 19 mm
- Standard accessories: battery, case, instructions for use
- Flat battery indicator



Code	Model	Description
VP116800	VE 6054	Clamp meter for dispersed currents

## GENERAL CHARACTERISTICS

Function	Capacity	Reading precision	Resolution	Protection
Current	AC 200 mA	± (1.2% rdg + 5 dgt)	0.1 mA	-
	20 A	± (1.2% rdg + 5 dgt)	0.01 A	300 A (60 s)
	200 A	± (1.2% rdg + 5 dgt)	0.1 A	300 A (60 s)

## REFERENCE STANDARDS

Compliance with Community Directives: 2006/95/EC (Low Voltage) and 2004/108/EC (E.M.C.)  
is declared with reference to the following standards: • Safety: EN 61010-1 • E.M. Compatibility: EN 55014 / EN 61000-6-1