

Movement detectors

SENSOR 360

DIMENSIONS (mm)

CONNECTION DIAGRAM

Ceiling-mounting movement detector that identifies the movement of people, vehicles, objects and activates a lighting system.

- 1 Installation base
- 2 Sensor




Front view



Side view



Diagram



TIME AND MANAGEMENT

TECHNICAL INFORMATION

CEILING-MOUNTING DETECTOR

- Sensor to adjust the level of luminosity with which to operate
- Range of action: 3.5 m / 360° (with an installation at a height of 2.5 m)
- Power supply: 230 V - 50 Hz
- Ceiling-mounting
- Degree of protection: IP20
- Adjustable operating time: 3 s ÷ 10 min

GENERAL CHARACTERISTICS

Power supply	V AC	230
Frequency	Hz	50
Absorption	W	2
Range of action (with h = 2.5m)	m	3.5
Angle		360°
Incandescent lamps	W	1000
Halogen lamps	W	1000
Degree of protection	IP	20
Operating time		3 s ÷ 10 min

Code	Model	Description	Range of action
VP403000	SENSOR 360	Ceiling-mounting movement detector	3.5 m / 360°

REFERENCE STANDARDS

Compliance with Community Directives: 2014/35/EU (LVD) • 2014/30/EU (EMCD) is declared with reference to the following standards: EN 60669-2-1